Uniden® UH8010S+ANT

UHF CB MOBILE

18+ km°





















UNIDEN'S PREMIUM MASTER SCAN™ TECHNOLOGY

Master Scan[™] Offers Minimal Disruptions for Continuous Communication. It Includes the Following Features.

Dynamic Switching:


Continual communication without interruption is possible by dynamically switching to unused channels. This network scan function scans for other radios that share the same CTCSS or DCS tone. When the radio detects a signal with no code, or the wrong code, it switches to an unused channel when transmitting. By scanning only group channels, radios in the network will be able to detect and receive group transmissions — continual communication without interruption.

Pre-batched Group Channels:

Avoid complicated settings by preloading group channels.

Lightning Encode:

An advanced rectifier circuit enables the radio to decode CTCSS/DCS quickly.





Minimal Disruptions for Continuous Communication

Please note: CH 22 & 23 are used for telemetry and telecommand applications, voice communications are not permitted on these channels and transmission is inhibited. CH 61, 62 & 63 are for future use and are receive only channels.

•••••••

- ** Allows the radio to operate via a local repeater station, if available, which re-transmits your signal over a wider area. Up to an extra 30 100km depending on location, height and availability of local repeater station.
 Specifications subject to change without notice.
- # 18+km: Typical Range Line of Sight.
- Δ $\,$ One year warranty for the included accessories.

SCAN & DISCOVER



FOLLOW US



@UnidenAustralia



Uniden-Australia

UH8010S + ANT SPECIFICATIONS

UHF CB MOBILE	UH8010S+ANT
Output Power	5 Watts
Number of UHF-CB Channels*	80*
Frequency Range (in 12.5kHz steps)	
JHF-CB	476.425MHz – 477.4125MHz
Master Scan™	•
Channel Width	12.5kHz (Narrowband)
Power Source (nominal)	13.8V
Microphone	MK800 (included)
Microphone Condenser	Electret
Base Speaker (maximum power)	2W
AVS circuitry [†]	•
Digital Coded Squelch (DCS)	104
nterference Eliminator CTCSS	38
Range Extender Duplex Capability**	•
_CD Display	Segment
Backlit Keypad and LCD	Yes
Backlight Colours	Blue, Red, Purple (Magenta), Green, Cyan, Yellow, Clear (White)
Flip LCD	•
External Speaker Jack	•
Flip Mounting	•
FX/RX Indicator	•
Scanning Receiver Functions	
Channel Memory	•
Open Scan	•
Group Scan (with Priority Watch)	•
Key Beep On/Off	•
Roger Beep	•
Calling Tones	5
nstant Channel	•
Monitor Function	•
Auto Squelch	•
Antenna	AT870
mpedance	50 OHM
Gain YOM D	+6.5dB
/SWR	< 1.5 : 1 (476.42MHz – 477.4MHz) Vertical
Polarisation Radiation	vertical Omni Directional
Material	Fibreglass & Stainless Steel
Cable	RG58 C/U 5m
Termination	FME + FME to UHF adaptor

INCLUDED IN THE BOX

1 x UH8010S Radio
1 x Heavy Duty Microphone
1 x Microphone Hanger
1 x DC Power Cord
1 x Owner's Manual
1 x AT-870 6.5dB Antenna with 5m cable

OPTIONAL ACCESSORIES

BM100: Bluetooth Microphone
MS-200: External Speaker