

Uniden®

GUARDIAN 



DIY INSTALLATION

FULL HD TECHNOLOGY SECURITY SYSTEMS

FULL HD HYBRID DIGITAL VIDEO RECORDERS
WIRED + WIRELESS IP CAMERA CAPABILITY

 **HYBRID** 

WIRED + WIRELESS READY

**FULL
HD**
1080P*

Uniden® GUARDIAN™

2 UP TO 2 TB
INTERNAL STORAGE



VIEW ON TV



NIGHT VISION
UP TO 20 METRES



24/7
SURVEILLANCE



USB BACKUP



PUSH
NOTIFICATIONS &
EMAIL ALERTS



RECORD & WATCH
FOOTAGE VIA
SMARTPHONE
OR TABLET

INSIDE THE BOX

Each model is made up of various quantities of the following products:



Weatherproof®
Outdoor Camera



Full HD DVR Unit



HDMI Cable



Ethernet Cable



DVR Power Supply



1 to 4 Power Supply



BNC & Power Cable (18m)



Mouse



Mounting Kit



Security Sticker



Enhance the flexibility of your system with OPTIONAL WIRELESS CAMERAS

Ideal for areas where installation of network cables is difficult.



APP CAM 34
Dome Wireless
(IP) Camera



APP CAM 35
Weatherproof Outdoor
Wireless (IP) Camera



APP CAM 36
Indoor Pan & Tilt
Wireless (IP) Camera

HYBRID RANGE



FULL HD SECURITY SYSTEM IN THE PALM OF YOUR HAND

Enjoy the comfort of having the control in the palm of your hand – push notifications with instant alerts from anywhere in the world via our FREE app for smartphones & tablets.

REMOTE VIEWING
Anytime. Anywhere in the World.



GCVR 4H402

INCLUDES: 4 Wired Weatherproof Cameras + 2 Wireless Weatherproof IP Cameras



UP TO 16 WIRED CAMERAS

UP TO 8 IP CAMERAS (OPTIONAL)

ULTRA NIGHT VISION

With built-in Ultra Night Vision (UNV) & Full HD resolution, you might capture the important details that could lead to property recovery and even criminal conviction*.



INPUT PANELS

The number of Video IN ports vary between models





SPECIFICATIONS

SYSTEM

Main Processor	Embedded processor
Operating System	Embedded LINUX

VIDEO

Input	up to 16 channel, BNC Analog NTSC/PAL
Standard	HDCVI 1080P/720P HDCVI Camera
IP	Support 1080P/720P IP Camera

AUDIO

Input	1 channel, RCA
Output	1 channel, RCA
Two-way Talk	Reuse audio input/output channel

DISPLAY

Interface	1 HDMI, 1 VGA
Resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Display Split	1/4/8/9 & 16 for model GCVR 16H80
Privacy Masking	4 rectangular zones (each camera)
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

RECORDING

Video/Audio Compression	H.264/G.711
Record Rate	Main Stream: 1080P(up to 15fps)/ 720P, 960H, D1 (up to 25fps) Extra Stream: CIF/QCIF(up to 25fps)
Bit Rate	96~4096Kb/s
Record Mode	Manual, Schedule, Motion Detection
Record Interval	1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

VIDEO DETECTION & ALARM

Video Detection	Motion Detection, Video Loss & Camera Blank
-----------------	---

PLAYBACK & BACKUP

Sync Playback	1/4/9 & 16 for model GCVR 16H80
Search Mode	Time/Date, Motion Detection & Exact search (accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Internal SATA burner/Network

NETWORK

Ethernet	RJ-45 port (10M/100M + 1000M for model GCVR 16H80)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, SNMP, P2P
Max. User Access	128 users
Smart Phone	iPhone®, iPad®, Android

STORAGE

Internal HDD	1 SATA port, up to 2TB* Included
--------------	----------------------------------

AUXILIARY INTERFACE

USB Interface	2 USB2.0 ports (1 USB2.0 + 1 USB3.0 port for model GCVR 16H80)
RS485	1 port, For PTZ Control

GENERAL

Power Supply	DC12V/2A
Working Environment	-10°C ~+55°C / 10%~90%RH / 86~106kpa

CAMERA

Image Sensor	1/2.7" CMOS
Effective Pixels	1920x1080 2 Megapixel
Electronic Shutter	1/50s~1/100,000s
Video Frame Rate	up to 25fps@1080P
Mini. Illumination	0.02Lux@F2.0, 0 Lux with IR on
Video Output	1-channel BNC HDCVI high definition video output

CAMERA FEATURES

Max. IR LEDs Length	20m
Colour	Day: Colour / Night: B/W

LENS

Focal Length	3.6mm fixed lens
Angle of View	H: 89.9°
Mount Type	M12

AUDIO

Microphone	N/A
Audio Range	N/A

GENERAL

Power Supply	DC12V±20%
Power Consumption	Max 3.5W
Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)
Transmission Distance	Over 500m via 75-3 coaxial cable
Ingress Protection	IP66+
Material	Plastic



For complete range details, scan QR Code or visit Uniden at: uniden.com.au or call **1300 366 895** today.

FOLLOW US

