# Uniden®

# UHF CB MOBILE 80 Channel\* 5W UH5040R

12 🗲 24

Voltage Suitable For Any Vehicle



Compact Size



ick Release Bracket Sp





**5 Year Warranty** 

BUILT RUGGED

## **Uniden**<sup>®</sup>

### UHF CB MOBILE UH5040R



#### 80 UHF Narrowband Channels\*:

Choose from up to 80 frequencies to transmit and receive messages.

Compact Size: Cabinet size; 127mm (W) x 36mm (H) x 107mm (D)

#### **5 Year Warranty**

#### **5W Maximum TX Output Power:**

Maximum transmit power.

#### **Built-in AVS Circuitry:**

The Automatic Volume Stabiliser detects Narrowband and Wideband transmissions and automatically adjusts incoming audio to comparable levels.

Rotary Squelch Control: Control the squelch setting manually.

Rotary Volume Control: Control the volume setting manually.

#### **Rotary Channel Select**

Backlit LCD with Dimmer: Orange backlight with high/low dimmer control.

RF Level Bar Indicator: View the radio frequency signal strength.

**Instant Channel Programming One Touch Instant Channel** 

#### Recalling:

Instantly switch to your favourite channel and back with the touch of one microphone button.

Open Scan: Scans all the channels in memory and locks on active channels.

#### Group Scan (GS) with Priority

Channel Watch: Allows the user to select the channels they wish to monitor / listen to in a group, along with a priority channel (priority watch).

#### Range Extender (Duplex) Capability:

Allows operation via a local UHF repeater station, if available, which re-transmits your signal over a wider area. Up to an extra 30-100km depending on location, height and availability of repeater station.

#### **Busy Channel Lock-out Function:**

Disables your transmitter while activity is detected on the channel.

Roger Beep: Confirmation tone indicates the completion of your transmission.

Call Tone Function: Choose from one of 5 wake-up tones to initiate your transmission with the touch of one microphone button.

#### **CTCSS (Continuous Tone Coded** Squelch System) and DCS (Digital Coded Squelch) Codes: Choose

from 38 (CTCSS) and 104 (DCS) digital codes that can be sent with your transmission. The code is recognised by the selected receivers enabling them to receive the transmission. Receivers that do not recognise the code remain silent therefore blocking out unwanted conversations.

#### External Speaker Jack

**Designed & Engineered in Japan** 

**Built Rugged for Australian and New Zealand Conditions** 

Please note: In the UHF CB expansion 80 channels are available for use. CH 22 & 23 are used for telemetry and telecommand applications, voice communications are not permitted on these channels and transmission is inhibited. CH 61, 62 & 63 are guard channels and are unavailable for use.

\* 18km: Typical Range Line of Sight.

One year warranty on any included accessories. Specifications subject to change without notice.

For full range & details call 1300 366 895, scan QR code or visit uniden.com.au







